

What Data Do We Have?

Challenge Solution

```
1 //*****  
2 // File name: hello.cpp  
3 // Author: Chadd Williams  
4 // Date: 09/01/2006  
5 // Purpose: This program asks for a users name and then  
6 // displays a personalized message.  
7 //*****  
8 #include <iostream>  
9 #include "stdafx.h"  
10 #include <string>  
11 using namespace std;  
12  
13 int main()  
14 {  
15     string name;  
16  
17     cout << "What is your name? " << endl;  
18  
19     cin >> name;  
20  
21     cout << "Hello " << name << "!" << endl;  
22  
23     return 0;  
24 }
```

Today

- On Wednesday I showed you a C++ program that displays a personalized message to the user
- What are the main components of that program?
- Today we will
 - learn how C++ stores data
 - Some of the different types of data that C++ can store

main Function

- `int main()`
- Marks the beginning of a function
- A function is a group of one or more programming statements
- The set of parentheses indicate a function
- C++ is case-sensitive
 - `int Main()` is incorrect!!

cout Object

- `cout` object is the standard output object
- The monitor is the standard output device
- `cout` is a stream object and works with streams of data
 - Streams of characters

cout Object

- Output operator (insertion operator): `<<`
- Standard output (monitor screen): `cout`
- The value to the right of the operator (right operand) is displayed on the screen
 - If the right operand is within double quotes, then it is output exactly as it appears
 - The exception is if it is an escape character `\`
 - If the right operand is a variable or constant, then the value of that variable or constant is output

cout Object

- What is the output?

```
cout << "Enter the distance in miles" << endl;
```

```
cout << "The distance in kilometers is " << kms << endl;
```

- You must always use the insertion operator `<<` to separate the different components you wish to output
- `endl` will move the cursor to a new line
- All output statements must end in a semicolon
- Output strings within double quotes `" "` should always appear on one line

cout Object

- << is used to separate the different output items
- Example:
 - `cout << "Type your name, then press enter" << endl;`
- It is illegal to break up the string literals across lines
 - `cout << "Type your name, then`
 - `press enter" << endl;`
 - Is illegal!!

cout Object

- Other ways of outputting the same message

```
cout << "Type your name, " << "then press enter" << endl;
```

```
cout << "Type your name, ";
```

```
cout << "then press enter" << endl;
```

- Everything will output to the same line unless you specify otherwise

Problem

- What is the output?

```
cout << "My name is: ";  
cout << "Doe, Jane." << endl;  
cout << "I live in ";  
cout << "Ann Arbor, MI ";  
cout << "and my zip code is "  
<< 48109 << ". " << endl;
```

Problem

- Write the C++ statements necessary to perform the following operation
 - Display the message below onto the screen
"C++ is a useful
language to know"

Escape Characters

- These are special characters that can be output
- They are always preceded by a backslash \
- Examples of escape characters include:
 - `\n`: moves the cursor to the beginning of the next line
 - Equivalent to `endl`
 - `\r`: moves the cursor to the beginning of the current line
 - `\t`: moves the cursor to the next tab stop
 - `\\`: displays the backslash
 - `\"`: outputs the double quotes

Examples

- What is the output?
 - `cout << "This is a C++ program\n";`
 - `cout << "This is a \nC++ program";`
 - `cout << "\\\"This is a C++ program\"";`
 - `cout << "This is a\tC++\tprogram";`

Variables

- A variable is a named storage location for holding data
- Part of the job of programming is to determine how many variables a program will need
- Let's look at program 2-7 on p. 41, also on the next slide

Variables

```
1 #include "stdafx.h"
2 #include <iostream>
3
4 using namespace std;
5
6 int main()
7 {
8     int number;
9
10    number = 5;
11    cout << "The value of number is " << "number" << endl;
12    cout << "The value of number is " << number << endl;
13
14    number = 7;
15    cout << "Now the value of number is " << number << endl;
16
17    return 0;
18 }
```

Variable Definition

- **int number;**
- Tells the compiler
 - The variable's type (int)
 - The variable's name (number)
- int is short of integer
- Variable definitions end with a semicolon

Assignment

- `number = 5;`
- `=` is an operator that copies the value on its right into the variable on its left
- The item to the left of the `=` operator must be a variable

Program Output

- What do you think is the program's output?

String Literals

- Placing quotations around a variable name changes it to a string literal

```
cout << "The value of number is " << "number" << endl;
```

- What is the output of the statement
 - `cout << "endl" ;`

Exercises

- Which of the following are legal C++ statements?
 - `a = 7;`
 - `7 = a;`
 - `7 = 7;`

Summary

- In today's lecture we covered
 - `main` function
 - `cout` object
 - How data that is used by a program can be declared and stored
- We have covered p. 31 - 45 of your textbook