

# Chapter 14

## Friends of Classes

---

- Reading pp.819-823, 831-857
- Good Problems to work: p. 823 14.1, 14.2, 14.3, 14.4, 14.5, 14.6, 14.7; p. 845 14.14, 14.19; p. 857 14.21

# Friends of Classes

---

- Only the member functions of a class have direct access to the private data members of the class
- `friend` functions are friends of the class that are defined outside of the class but still have access to private data members

# Friends of Classes

---

- A **friend** function can be
  - a) a regular stand-alone function
  - b) a member of another class
  - c) an entire class

# friend Functions

- 
- The function prototype is placed in the class, preceded by the keyword **friend**
  - The function definition can be written anywhere without the class name (class::)
  - The function is able to directly access the private data members of the class

# Operator Overloading

---

- C++ allows overloading operators to work with class objects
- For example, we can overload the extraction operator `>>` and insertion operator `<<` for Rational objects

# Overloading Stream Operators

---

- Two classes named ostream and istream provide stream I/O.
- Definitions for >> and << are provided for the primitive datatypes such as int, float, char, and so on but not for programmer-defined types. Stream operators can be overloaded for our **Rational** class. As an example, we would like the following to have meaning:

```
Rational cR1 (3,1) ;
```

```
cout << "Enter a rational number:" ;  
cin >> cR1 ;
```

In particular, we would like to be able to enter a value such as 1/3 for cR1.

# Overloading Stream Operators

- The general format for overloading the stream operators is as follows:

```
class SomeClassName
{
    public:
        .....
        friend istream& operator>> (istream &cInput,
                                    ClassDef &cObject);
        friend ostream& operator<< (ostream &cOutput,
                                    const ClassDef &cObject);
    private:
        .....
};
```

# Overloading Stream Operators

---

- Note: For the stream extraction operator `>>` some `istream` object is passed to the operator function through **`cInput`** such as `cin`.
- Similarly, the stream insertion operator `<<` is passed some `ostream` object through **`cOutput`** such as `cout`.
- The function returns a modified stream so that the following chain can be executed correctly:
- `cin >> r1 >> r2; // What is the associativity of >>? Why?`
- Similar logic is used for the insertion operator `<<` function.



# Overload Insertion Operator <<

---

```
class Rational
{
    public:
        Rational (int = 0, int = 1);
        .....
        friend ostream& operator<< (ostream &cOutput,
                                     const Rational &cRational);
    private:
        ...
};
```

# Overload Insertion Operator <<

---

```
ostream& operator<< (ostream &cOutput,  
                    const Rational &cRational)  
{  
    cOutput << cRational.mNumerator << '/'  
           << cRational.mDenominator;  
  
    return cOutput;  
}
```

# Overload Problem for Rational

---

1. Overload the insertion operator <<
2. Overload the extraction operator >>
3. Overload the multiplication operator \*
4. Write a driver to test all functions including overloaded operators